

GTWY2000

移动桅柱式高空作业平台 (双桅)



Dingli GTWY 8-2000 GTWY 10-2000 GTWY 12-2000 GTWY 14-2000 GTWY 16-2000



安全工作载荷	300kg	300kg	250kg	200kg	150kg
最大工作人数	2	2	2	2	1
- 平台高于10m	/	/	/	1	1



H ₁ 最大工作高度	8.00m	10.00m	12.00m	14.00m	16.00m
H ₂ 最大平台高度	6.00m	8.00m	10.00m	12.00m	14.00m



A 整机长度	1.52m	1.52m	1.74m	1.81m	1.81m
B 整机宽度	0.81m	0.81m	0.81m	0.81m	0.81m
H ₃ 整机高度	1.86m	1.86m	1.86m	2.08m	2.36m
支腿展开尺寸(L/W)	1.82m/1.78m	1.82m/1.78m	2.45m/2.34m	2.45m/2.34m	2.45m/2.34m
工作平台尺寸(长×宽 C)	1.21m×0.60m	1.21m×0.60m	1.44m×0.60m	1.44m×0.60m	1.44m×0.60m
最小离地间隙	0.07m	0.07m	0.07m	0.07m	0.07m
轴距	1.17m	1.17m	1.41m	1.41m	1.41m



起升电机(AC)	110/230VAC/1.5kW	110/230VAC/1.5kW	110/230VAC/1.5kW	110/230VAC/1.5kW	110/230VAC/1.5kW
起升电机(DC)	12VDC/2.5kW	12VDC/2.5kW	12VDC/2.5kW	12VDC/2.5kW	12VDC/2.5kW



上升/下降速度	58/40sec	64/44sec	74/44sec	76/47sec	101/59sec
---------	----------	----------	----------	----------	-----------



蓄电池	2×12V/110Ah	2×12V/110Ah	2×12V/110Ah	2×12V/110Ah	2×12V/110Ah
充电器	12V/15A	12V/15A	12V/15A	12V/15A	12V/15A



轮胎(前轮)	8in	8in	8in	8in	8in
轮胎(后轮)	7in	7in	7in	7in	7in



整机重量(AC)	600kg	624kg	764kg	844kg	905kg
整机重量(DC)	636kg	662kg	784kg	870kg	925kg

标准配置

- 带传感器的调平支腿
- 紧急停止按钮
- 充电指示灯
- 限位开关
- 双控制器操作
- 紧急下降系统
- 水平指示器
- 标准叉车孔
- 运输绑定孔
- 动作蜂鸣
- 双手控制
- 油管防爆系统

选装配置

- 超重传感器
- 连接到平台的AC电源
- 平台工作灯
- DC电源带充电器



自动平台升降系统



带互锁的旋开支腿



带支腿灯的控制器

