

型号	=电动款 =柴油款	BT30ERT BT30RT	BT28ERT BT28RT	BT26SERT BT26SRT	BT26ERT BT26RT	BT24ERT BT24RT	BA28ERT BA28RT	BA24ERT BA24RT
类型	直 臂 式						曲 臂 式	
尺寸								
最大工作高度	30.30m	28.60m	26.70m	26.32m	24.80m	28.10m	24.30m	
最大平台高度	28.30m	26.60m	24.70m	24.32m	22.80m	26.10m	22.30m	
最大水平伸距	22.70m	21.30m	19.20m	18.90m	17.30m	18.80m	16.50m	
整机长度(收拢状态) A	12.25m	11.66m	10.83m	10.82m	10.25m	11.83m	9.83m	
整机长度(装箱状态)	11.96m	11.82m	11.12m	10.77m	10.81m	12.03m	10.03m	
整机宽度(收拢状态) B					2.50m			
整机宽度(装箱状态)					2.28m			
整机高度(收拢状态) C					2.89m			
整机高度(装箱状态)					2.57m			
工作平台尺寸(长×宽)					2.44m×0.9m			
转台尾摆					1.61m			
最小离地间隙 D					0.41m			
轴距 E					2.8m			
最小转弯半径(内轮/外轮)					1.87m/3.22m			
轮胎					385/45-28			
最大跨越高度						9.14m		
最大下探深度						6.61m	4.03m	
性能								
安全工作载荷(不受限/受限)	300kg/454kg	454kg				250kg	300kg	
最大工作人数	3					2		
最大爬坡能力	30% 45%	30% 45%	30% 45%	30% 45%	30% 45%	30% 45%	30% 45%	30% 45%
收拢状态最大行驶速度	6km/h							
起升状态最大行驶速度	1.1km/h							
底盘工作最大允许角度	X-5°/Y-5°							
转台回转角度	360°连续							
平台摆动角度	180°							
小臂变幅角度	130°	135°	130°	135°				
重量								
整机重量	18900kg	18400kg	16600kg	16090kg	14300kg	18300kg	17100kg	
动力								
动力源	 锂电池 520Ah/80V 充电器 5kW/80V,12V				 柴油发动机 Deutz TD2.9 L4 55.4kW			
液压油箱	150L							

